



**Crewsaver**<sup>®</sup>  
Safer By Design<sup>®</sup>

**Newtons**

- 290
- 275
- 190
- 150

**Type**

- Buoyancy Aid
- Lif Jacket

**Floatation**

- Inflatable
- Foam
- Combination

**Chambers**

- Single
- Twin

**Harness**

- Fall Arrest
- Deck

**Cover**

- Fire Resistant
- Wipe Clean
- Heavy Duty

**Approval**

- ISO approved
- 12402-3



**FUSION 3D**<sup>®</sup>

[www.crewsaver.com](http://www.crewsaver.com)

# ERGOFIT 190<sup>PRO</sup>

The ErgoFit 190N PRO maintains all of the high specification safety features on the inside as the 190N OS, whilst minimising features on the outside. A 3D-moulded lifejacket with the advanced specification on the inside to excel for all coastal and offshore water users.

With its intelligent cut-away profile, it allows you total mobility, leaving your body, limbs and hands unhindered and free to move, work and perform. Being easy to wear, versatile, stylish and completely functional, it is ideally suited to recreational users and the marine work environment alike.

## KEY FEATURES

- A transparent 'window' on the front of the jacket showing the status of the inflator, allowing you to check your lifejacket is in working order without having to unpack and repack the jacket
- Dual buckle system and side waist adjusters, uniquely designed to ensure swift donning - essential if the wind gets up and it's all hands on deck
- Dual light weight soft loop D-rings for attaching safety line
- Unique bladder distribution, providing turning solutions in less than three seconds and allows you to move your arms freely
- A built in inflatable chin support tilts your neck back and keeps your airways clear
- AIS compatible, allows for automatic activation on inflation



Code	Description
9115BKAP	Automatic with Harness, Light and Hood
9115BKHP	Hammar with Harness, Light and Hood



QUICK BURST ZIP



3D SHAPE FOR UNRIVALLED FIT



EXCEPTIONAL TURNING SPEEDS



AIS COMPATIBLE



FREEDOM OF MOVEMENT



UNIQUE CHIN SUPPORT



PROVIDES 180% OF BUOYANCY



INDICATOR WINDOW



BS EN ISO 12402-3

